

BAGGAGE CART ZW-30-D2400





AKS Baggage Carts are designed for reliable, safe and efficient baggage transportation in demanding airport environments. Built with a robust welded steel frame with hot-dip galvanized finish for long-term corrosion protection, or a two-layer C4-B paint class, making them suitable for operation in harsh climatic and coastal environments.

Engineered to withstand intensive daily ground handling operations while minimizing maintenance requirements and maximizing service life.

The carts are available in both open and covered (rooftop) configurations and can be customized to meet specific customer requirements, including dimensions, payload capacity, flooring type, side barriers, wheel options, coupling systems, and corporate branding.

Manufactured in accordance with applicable standards (Machinery Directive 2006/42 EC, EN 1915-1:2023, EN 12312-11) supplied with CE certification, and backed by a 24-month warranty, ensuring dependable performance throughout their operational lifetime.

Technical Specification:

- Load surface dimensions: 1500 mm × 2,400 mm
- Overall dimensions: 2900 × 1510 × 1760 mm
- Loading height: 530 mm
- Maximum payload capacity: 1200 kg
- Unladen weight: 420 kg
- Maximum speed: 25 km/h
- Solid tyres size: 4.00–8
- Rooftop made of galvanized steel profiles
- Tarpaulin with hooks, mounted on two sides
- Parking brakes activated when the tow bar is raised
- Load platform made of 21 mm waterproof plywood
- Hot-dip galvanized corrosion-resistant frame
- Tow bar equipped with a damping spring and lower bumper
- Automatic rear coupling
- CE certificate