

CARGO DOLLY CZ-11-D4200





AKS Cargo Dollies are designed for the safe, efficient, and dependable transport of ULD containers throughout airport cargo terminals and ramp operations. Engineered for high-load applications, they combine a durable steel structure with precision-manufactured roller systems to ensure smooth cargo transfer and reliable performance in demanding environments.

Available in a wide range of configurations, AKS Cargo Dollies can be tailored to suit different ULD types, operational requirements, and airport standards. Their robust construction, corrosion-resistant finish, and low-maintenance design provide exceptional durability, helping ground handling operators maximize productivity while minimizing lifecycle costs.

Main specifications of CZ-11-D4200 model:

- Suitable for LD1, LD2, LD3, LD4, LD8
- Hot deep galvanized finish
- Solid tyres
- Wheel size 4.00 X 8"
- Automatic Ringfeder coupling
- Tow eye diameter Ø40 mm
- Ø65 mm cargo rollers, spring loaded
- Maximum speed 25 km/h
- Load Capacity 2600 kg
- Empty weight 850 kg
- Dimensions 4130 x 1760 x 516 mm
- Break on front wheels, activated when towbar raised
- Spring compression on the towbar for safe and slow collapsing
- 2-wheel turntable steering
- 24 month guarantee